

according to 1907/2006/EC, Article 31

3026516

Reviewed on: 26/06/2023

Printing date: 26/06/2023

SECTION 01: Identification of the substance/mixture and of the company undertaking

• 1.1 Product identifier

- *Trade name:*
OWEDUR 5037-99 HARDENER FOR HIGH GLOSS LACQUER
- Article number / Safety Data Sheet:
H50370
- *1.2 Relevant identified uses of the substance or mixture and uses advised against*
- Application of the substance / the preparation
Coating material

• 1.3 Details of the supplier of the safety data sheet

- *Manufacturer/Supplier:*
Teknos AG
Industriestrasse 7
LI-9487 Gamprin-Bendern
T +423 375 94 00
F +423 375 94 99

- *Further information obtainable from:*
Product safety department. e-mail address: li-sdb@teknos.com
- *1.4 Emergency telephone number:*
Swiss Toxicological Information Centre, CH-8032 Zürich Emergency telephone: +41 (0)44 251 51 51 (International)

SECTION 02: Hazards identification

- *2.1 Classification of the substance or mixture*
- Classification according to Regulation (EC) No 1272/2008



GHS02

Flam. Liq. 2 - H225 Highly flammable liquid and vapour.



GHS07

Acute Tox. 4 - H332 Harmful if inhaled.
Skin Irrit. 2 - H315 Causes skin irritation.
Eye Irrit. 2 - H319 Causes serious eye irritation.
Skin Sens. 1 - H317 May cause an allergic skin reaction.
STOT SE 3 - H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

- *2.2 Label elements*
- Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms



GHS02

GHS07

- Signal word
Danger

- Hazard-determining components of labelling:
polyisocyanate aliphatic / n-butyl acetate / xylene / Polyisocyanate aromatic
- Hazard statements
H225 Highly flammable liquid and vapour.
H332 Harmful if inhaled.
H315 Causes skin irritation.
H319 Causes serious eye irritation.

(continued on page 2)

according to 1907/2006/EC, Article 31

3026516

Reviewed on: 26/06/2023

Printing date: 26/06/2023

PRODUCT : OWEDUR 5037-99 HARDENER FOR HIGH GLOSS LACQUER

(continued of page 1)

- H317 May cause an allergic skin reaction.
H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. As from 24 August 2023 adequate training is required before industrial or professional use.
EUH204 Contains isocyanates. May produce an allergic reaction.
- Precautionary statements
 - P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 - P233 Keep container tightly closed.
 - P240 Ground and bond container and receiving equipment.
 - P302+P352 IF ON SKIN: Wash with plenty of water.
 - P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 - P501 Dispose of contents/container in accordance with local/regional/ national/international regulations.
 - **2.3 Other hazards**
 - Results of PBT and vPvB assessment
 - PBT:
 - Not applicable.
 - vPvB:
 - Not applicable.





SECTION 03: Composition/information on ingredients

• **3.2 Chemical characterization: Mixtures**

• **Description:**

Mixture of substances listed below with nonhazardous additions.

• **Dangerous components:**

CAS Number		%
141-78-6	ethyl acetate EC number: 205-500-4 Record number 01-2119475103-46 	10,00- 25,00
123-86-4	n-butyl acetate EC number: 204-658-1 Record number 01-2119485493-29 	10,00- 25,00
1330-20-7	xylene EC number: 215-535-7 Record number 01-2119488216-32 	10,00- 25,00
* 100-41-4	ethylbenzene EC number: 202-849-4 Record number 01-2119489370-35 	1,00- 5,00
108-65-6	2-methoxy-1-methylethyl acetate EC number: 203-603-9 Record number 01-2119475791-29 substance with a Community workplace	1,00- 5,00

(continued on page 3)

according to 1907/2006/EC, Article 31







3026516

Reviewed on: 26/06/2023

Printing date: 26/06/2023

PRODUCT : OWEDUR 5037-99 HARDENER FOR HIGH GLOSS LACQUER

(continued of page 2)

	exposure limit.	
	 Flam. Liq. 3 - H226	
28182-81-2	polyisocyanate aliphatic	25,00- 40,00
	EC number: 500-060-2	
	Record number 01-2119485796-17	
		
822-06-0	hexamethylene-di-isocyanate	0,0015- 0,50
*	EC number: 212-485-8	
*	Record number 01-2119457571-37	
*		
*	Reaction mass of ethylbenzene and xylene	1,00- 5,00
*		
53317-61-6	Polyisocyanate aromatic	5,00- 10,00
*		
26471-62-5	m-tolyldiene diisocyanate	0,0015- 0,50
*	EC number: 247-722-4	
*	Record number 01-2119454791-34	
*		
*	Resp. Sens. 1; H334: C >= 0,1 %	

• **Additional information:**

For the wording of the listed risk phrases refer to section 16.

SECTION 04: First aid measures

- 4.1 Description of first aid measures
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.

(continued on page 4)

according to 1907/2006/EC, Article 31

3026516

Reviewed on: 26/06/2023

Printing date: 26/06/2023

PRODUCT : OWEDUR 5037-99 HARDENER FOR HIGH GLOSS LACQUER

(continued of page 3)

- Immediately rinse with water.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**
Do not induce vomiting; call for medical help immediately.
- **Information for doctor:**
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 05: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:**
Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:**
Mouth respiratory protective device.
Do not inhale explosion gases or combustion gases.
- **Additional information**
Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 06: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
In case of seepage into the ground inform responsible authorities.
In case of gas release or seepage into the ground inform responsible authorities.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 07: Handling and storage

- **Handling:**
- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Take note of emission threshold.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Prevent impact and friction.

(continued on page 5)

according to 1907/2006/EC, Article 31

3026516

Reviewed on: 26/06/2023

Printing date: 26/06/2023

PRODUCT : OWEDUR 5037-99 HARDENER FOR HIGH GLOSS LACQUER

(continued of page 4)

- 7.2 Conditions for safe storage, including any incompatibilities
- **Storage:**
- Requirements to be met by storerooms and receptacles:
Store only in the original receptacle.
- Information about storage in one common storage facility:
Not required.
- Further information about storage conditions:
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **7.3 Specific end use(s)**
No further relevant information available.

SECTION 08: Exposure controls/personal protection

- 8.1 Control parameters
- **Ingredients with limit values that require monitoring at the workplace:**

141-78-6 ethyl acetate

WEL

Short-term value	1468	mg/m ³
	400	ppm
Long-term value	734	mg/m ³
	200	ppm

123-86-4 n-butyl acetate

WEL

Short-term value	966	mg/m ³
	200	ppm
Long-term value	724	mg/m ³
	150	ppm

1330-20-7 xylene

WEL

Short-term value	441	mg/m ³
	100	ppm
Long-term value	220	mg/m ³
	50	ppm

Sk; BMGV

100-41-4 ethylbenzene

WEL

Short-term value	552	mg/m ³
	125	ppm
Long-term value	441	mg/m ³
	100	ppm

Sk

108-65-6 2-methoxy-1-methylethyl acetate

WEL

Short-term value	548	mg/m ³
	100	ppm
Long-term value	274	mg/m ³

(continued on page 6)

according to 1907/2006/EC, Article 31

3026516

Reviewed on: 26/06/2023

Printing date: 26/06/2023

PRODUCT : OWEDUR 5037-99 HARDENER FOR HIGH GLOSS LACQUER

(continued of page 5)

	50	ppm
Sk		
* 822-06-0	hexamethylene-di-isocyanate	
* WEL		
* Short-term value	0.07	mg/m3
* Long-term value	0.02	mg/m3

* **Sen; as -NCO**

- Ingredients with biological limit values:

1330-20-7 **xylene**

BMGV**650 mmol/mol creatinine****Medium: urine****Sampling time: post shift****Parameter: methyl hippuric acid*** **822-06-0** **hexamethylene-di-isocyanate*** **BMGV*** **1 µmol creatinine/mol*** **Medium: urine*** **Sampling time: At the end of the period od exposure*** **Parameter: isocyanate-derived diamine**

- *Additional information:*

The lists valid during the making were used as basis.

- *8.2 Exposure controls*

- **Personal protective equipment:**

- *General protective and hygienic measures:*

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Avoid contact with the eyes and skin.

Do not eat or drink while working.

Be sure to clean skin thoroughly after work and before breaks.

- *Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Suitable respiratory protective device recommended.*

- *Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Protective gloves Impervious gloves*

- *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- *Penetration time of glove material*

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 374 part III are not performed under practical conditions.

Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

- *Eye protection: Safety glasses Tightly sealed goggles*

- *Body protection: Protective work clothing*

GB

(continued on page 7)

according to 1907/2006/EC, Article 31

3026516

Reviewed on: 26/06/2023

Printing date: 26/06/2023

PRODUCT : OWEDUR 5037-99 HARDENER FOR HIGH GLOSS LACQUER

(continued of page 6)

SECTION 09: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Appearance:

Form:	Liquid
Colour:	According to product specifica
Odour:	Characteristic Characteristic
Odour threshold:	Not determined.

Change in condition

Initial boiling point and boiling range: 77 °C

Flash point: -1 °C

Flammability (solid, gas): Not applicable.

Ignition temperature: 425 °C

Decomposition temperature: Not determined.

Auto-ignition temperature: Not determined.

Explosive properties: Not determined.

Explosion limits:

Lower: 1 Vol %

Upper: 11 Vol %

Vapour pressure: at 20 °C 6,7000 mbar at 50 °C 55,0000 mbar

Density: 0,9900 g/cm3

Solubility in / Miscibility with

water: Not determined.

Viscosity:

. Not determined.

. at 20 °C

9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity**
No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**
No dangerous reactions known.
- **10.4 Conditions to avoid**
No further relevant information available.
- **10.5 Incompatible materials:**
No further relevant information available.
- **10.6 Hazardous decomposition products:**
No dangerous decomposition products known.

GB

(continued on page 8)

according to 1907/2006/EC, Article 31

3026516

Reviewed on: 26/06/2023

Printing date: 26/06/2023

PRODUCT : OWEDUR 5037-99 HARDENER FOR HIGH GLOSS LACQUER

(continued of page 7)

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**
- **LD/LC50 values relevant for classification:**

141-78-6 ethyl acetate
 Oral, LD50: 5620 mg/kg (Rabbit)
 Inhalative, LC50/4h: 1600 mg/l (rat)

123-86-4 n-butyl acetate
 Oral, LD50: 13100 mg/kg (rat)
 Dermal, LD50: >5000 mg/kg (Rabbit)
 Inhalative, LC50/4h: >21 mg/l (rat)

1330-20-7 xylene
 Oral, LD50: 4300 mg/kg (rat)
 Dermal, LD50: 2000 mg/kg (Rabbit)

100-41-4 ethylbenzene
 Oral, LD50: 3500 mg/kg (rat)
 Dermal, LD50: 17800 mg/kg (Rabbit)

122-51-0 triethyl orthoformate
 Dermal, LD50: 20000 mg/kg (Rabbit)

108-65-6 2-methoxy-1-methylethyl acetate
 Oral, LD50: 8532 mg/kg (rat)
 Inhalative, LC50/4h: 35,7 mg/l (rat)

822-06-0 hexamethylene-di-isocyanate
 Oral, LD50: 738 mg/kg (rat)
 Dermal, LD50: 593 mg/kg (rat)

- **Primary irritant effect:**
- Skin corrosion/irritation
 Irritant to skin and mucous membranes.
- Serious eye damage/irritation
 Irritating effect.
- **Respiratory or skin sensitisation**
 Sensitisation possible through skin contact.
- **Additional toxicological information:**
 The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
 Harmful
 Irritant
- **11.2 Information on other hazards**
- **Endocrine disrupting properties**
 None of the ingredients is listed.

SECTION 12: Ecological information

- **12.1 Toxicity**
- Aquatic toxicity:
 No further relevant information available.
- **12.2 Persistence and degradability**
 No further relevant information available.
- **Behaviour in environmental systems:**
- **12.3 Bioaccumulative potential**
 No further relevant information available.
- **12.4 Mobility in soil**
 No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:**
 Not applicable.

(continued on page 9)

according to 1907/2006/EC, Article 31

3026516

Reviewed on: 26/06/2023
Printing date: 26/06/2023

PRODUCT : OWEDUR 5037-99 HARDENER FOR HIGH GLOSS LACQUER

(continued of page 8)

- *vPvB:*
Not applicable.
- **12.6 Other adverse effects**
No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **European and swiss waste code**
08
WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01
wastes from MFSU and removal of paint and varnish
08 01 11
waste paint and varnish containing organic solvents or other hazardous substances
- **Uncleaned packaging:**
- **Recommendation:**
Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
ADR UN1263
IMDG UN1263
IATA UN1263
- **14.2 UN proper shipping name**
ADR 1263 PAINT RELATED MATERIAL
IMDG PAINT RELATED MATERIAL
IATA PAINT RELATED MATERIAL

- **14.3 Transport hazard class(es)**
ADR
Class 3 Flammable liquids.
Label 3



- IMDG
Class 3 Flammable liquids.
Label 3



- IATA
Class 3 Flammable liquids.

(continued on page 10)

according to 1907/2006/EC, Article 31

3026516

Reviewed on: 26/06/2023

Printing date: 26/06/2023

PRODUCT : OWEDUR 5037-99 HARDENER FOR HIGH GLOSS LACQUER

(continued of page 9)

Label

3



- **14.4 Packing group**

ADR II

IMDG II

IATA II

- **14.5 Environmental hazards:**

Not applicable.

- **14.6 Special precautions for user**

Warning: Flammable liquids.

Danger code (Kemler): 33

EMS Number: F-E,S-E

- **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

- **Transport/Additional information:**

Not applicable.

Excepted quantities (EQ): E2

Limited quantities (LQ) 5L

Transport category 2

Tunnel restriction code D/E

IMDG

Limited quantities (LQ) 5L

Excepted quantities (EQ) E2

- **UN "Model Regulation":**

UN 1263 PAINT RELATED MATERIAL, 3, II

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II
None of the ingredients is listed.
- REGULATION (EU) 2019/1148
- Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))
None of the ingredients is listed.
- Annex II - REPORTABLE EXPLOSIVES PRECURSORS
None of the ingredients is listed.
- REGULATION (EC) No 1907/2006 ANNEX XVII
Conditions of restriction: 3, 40

- **National regulations:**

- **Information about limitation of use:**

The above-mentioned manufacturer's information on the handling of isocyanates is contained in the safety data sheet of the product. The European Committee of Paint, Printing Ink and Artists 'Colours Manufacturers' Associations (CEPE) provides the following information on coatings isocyanates: Ready-to-use paints containing isocyanates may have an irritant effect on mucous membranes - especially on breathing organs - and cause hypersensitivity reactions. Inhalation of vapour or spray mist may cause sensitisation. When handling paints containing isocyanates, all precautions required for solvent-containing paints must be followed. Vapour and spray mist in particular should not be inhaled. Persons who are allergic, asthmatic, or prone to respiratory ailments should not work with isocyanate-containing paints.

(continued on page 11)

according to 1907/2006/EC, Article 31

3026516

Reviewed on: 26/06/2023

Printing date: 26/06/2023

PRODUCT : OWEDUR 5037-99 HARDENER FOR HIGH GLOSS LACQUER

(continued of page 10)

- *Technical instructions (air):*
- Class Share in %

III	18,10
II	20,00
I	0,12
- * *Waterhazard class:*
Water hazard class 2 (Self-assessment): hazardous for water.
- **15.2 Chemical safety assessment:**
A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases

EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
* H302	Harmful if swallowed.
* H304	May be fatal if swallowed and enters airways.
* H312	Harmful in contact with skin.
* H315	Causes skin irritation.
* H317	May cause an allergic skin reaction.
* H319	Causes serious eye irritation.
* H330	Fatal if inhaled.
* H332	Harmful if inhaled.
* H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
* H335	May cause respiratory irritation.
* H336	May cause drowsiness or dizziness.
* H351	Suspected of causing cancer.
* H373	May cause damage to organs through prolonged or repeated exposure.
* H412	Harmful to aquatic life with long lasting effects.
- **Department issuing MSDS:**
Environment protection department.
- **Abbreviations and acronyms:**
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
- * Data compared to the previous version altered.