

according to 1907/2006/EC, Article 31

2312523

Reviewed on: 28/06/2021

Printing date: 28/07/2021

SECTION 01: Identification of the substance/mixture and of the company undertaking

• 1.1 Product identifier

- *Trade name:*
SUPREMO KLARLACK 3990
- Article number / Safety Data Sheet:
W39900
- *1.2 Relevant identified uses of the substance or mixture and uses advised against*
- Application of the substance / the preparation
Coating material

• 1.3 Details of the supplier of the safety data sheet

- *Manufacturer/Supplier:*
* Teknos AG
* Industriestrasse 7
LI-9487 Gamprin-Bendern
T +423 375 94 00
F +423 375 94 99
- *Further information obtainable from:*
Product safety department. e-mail address: li-sdb@teknos.com
- *1.4 Emergency telephone number:*
* Swiss Toxicological Information Centre, CH-8032 Zürich Emergency telephone: +41 (0)44 251 51 51 (International)

SECTION 02: Hazards identification

- *2.1 Classification of the substance or mixture*
- Classification according to Regulation (EC) No 1272/2008



GHS02

Flam. Liq. 2 - H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 - H319 Causes serious eye irritation.
STOT SE 3 - H336 May cause drowsiness or dizziness.

- *2.2 Label elements*
- Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms



GHS02 GHS07

- Signal word
Danger

- Hazard-determining components of labelling:
n-butyl acetate / ethyl acetate
- Hazard statements
H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
EUH208 Contains BENZOTRIAZOL DERIVATIVES Index no. 607-176-00-3,
methyl methacrylate. May produce an allergic reaction.
- Precautionary statements
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.

(continued on page 2)

2312523

Reviewed on: 28/06/2021
 Printing date: 28/07/2021

PRODUCT : SUPREMO KLARLACK 3990

(continued of page 1)

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water shower.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P501 Dispose of contents/container in accordance with local/regional/ national/international regulations.

- **2.3 Other hazards**
- Results of PBT and vPvB assessment
- PBT:
Not applicable.
- vPvB:
Not applicable.

SECTION 03: Composition/information on ingredients

- **3.2 Chemical characterization: Mixtures**
- Description:
Mixture of substances listed below with nonhazardous additions.

• Dangerous components:

CAS Number		%
141-78-6	ethyl acetate EC number: 205-500-4 ⚠ Flam. Liq. 2 - H225; ⚠ Eye Irrit. 2 - H319-EUH066, STOT SE 3 - H336	15,00- 25,00
123-86-4	n-butyl acetate EC number: 204-658-1 ⚠ Flam. Liq. 3 - H226; ⚠ STOT SE 3 - H336	25,00- 40,00
1330-20-7	xylene EC number: 215-535-7 ⚠ Flam. Liq. 3 - H226; ⚠ Acute Tox. 4 - H312, Acute Tox. 4 - H332, Skin Irrit. 2 - H315	5,00- 10,00
100-41-4	ethylbenzene EC number: 202-849-4 ⚠ Flam. Liq. 2 - H225; ⚠ STOT RE 2 - H373, Asp. Tox. 1 - H304; ⚠ Acute Tox. 4 - H332	1,00- 5,00
80-62-6	methyl methacrylate EC number: 201-297-1 ⚠ Flam. Liq. 2 - H225; ⚠ Skin Irrit. 2 - H315, Skin Sens. 1 - H317, STOT SE 3 - H335	0,00- 0,50
78-83-1	butanol EC number: 201-148-0 ⚠ Eye Dam. 1 - H318; ⚠ Flam. Liq. 3 - H226; ⚠ Skin Irrit. 2 - H315, STOT SE 3 - H335-H336	0,00- 0,50
	BENZOTRIAZOL DERIVATIVES Index no. 607-176-00-3 EC number: 400-830-7 ⚠ Skin Sens. 1 - H317; ⚠ Aquatic	0,00- 0,50

(continued on page 3)

according to 1907/2006/EC, Article 31

2312523

Reviewed on: 28/06/2021

Printing date: 28/07/2021

PRODUCT : SUPREMO KLARLACK 3990

(continued of page 2)

108-65-6

Chronic 2 - H411

2-methoxy-1-methylethyl acetate

1,00- 5,00

EC number: 203-603-9

substance with a Community workplace exposure limit.

 Flam. Liq. 3 - H226

SECTION 04: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:**
Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. Then consult a doctor.
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**
Do not induce vomiting; call for medical help immediately.
- **Information for doctor:**
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 05: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:**
Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:**
Mouth respiratory protective device.
Do not inhale explosion gases or combustion gases.
- **Additional information**
Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 06: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

GB

(continued on page 4)

2312523

Reviewed on: 28/06/2021

Printing date: 28/07/2021

PRODUCT : SUPREMO KLARLACK 3990*(continued of page 3)***SECTION 07: Handling and storage**• **Handling:**• **7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Take note of emission threshold.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

• **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

• **7.2 Conditions for safe storage, including any incompatibilities**• **Storage:**• **Requirements to be met by storerooms and receptacles:**

Store only in the original receptacle.

• **Information about storage in one common storage facility:**

Not required.

• **Further information about storage conditions:**

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

• **7.3 Specific end use(s)**

No further relevant information available.

SECTION 08: Exposure controls/personal protection• **8.1 Control parameters**• **Ingredients with limit values that require monitoring at the workplace:**

141-78-6	ethyl acetate		
WEL			
	Short-term value	400	ppm
	Long-term value	200	ppm
123-86-4	n-butyl acetate		
WEL			
	Short-term value	966	mg/m3
		200	ppm
	Long-term value	724	mg/m3
		150	ppm
1330-20-7	xylene		
WEL			
	Short-term value	441	mg/m3
		100	ppm
	Long-term value	220	mg/m3
		50	ppm
	Sk; BMGV		
100-41-4	ethylbenzene		
WEL			
	Short-term value	552	mg/m3
		125	ppm
	Long-term value	441	mg/m3
		100	ppm
	Sk		
80-62-6	methyl methacrylate		
WEL			

(continued on page 5)

according to 1907/2006/EC, Article 31

2312523

Reviewed on: 28/06/2021

Printing date: 28/07/2021

PRODUCT : SUPREMO KLARLACK 3990

(continued of page 4)

	Short-term value	416	mg/m3
		100	ppm
	Long-term value	208	mg/m3
		50	ppm
78-83-1	butanol		
WEL			
	Short-term value	231	mg/m3
		75	ppm
	Long-term value	154	mg/m3
		50	ppm
108-65-6	2-methoxy-1-methylethyl acetate		
WEL			
	Short-term value	548	mg/m3
		100	ppm
	Long-term value	274	mg/m3
		50	ppm

Sk

- Ingredients with biological limit values:

1330-20-7 xylene**BMGV****650 mmol/mol creatinine****Medium: urine****Sampling time: post shift****Parameter: methyl hippuric acid**

- *Additional information:*

The lists valid during the making were used as basis.

- *8.2 Exposure controls*

- **Personal protective equipment:**

- *General protective and hygienic measures:*

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

Be sure to clean skin thoroughly after work and before breaks.

- *Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Suitable respiratory protective device recommended.*

- *Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Protective gloves Impervious gloves*

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 374 part III are not performed under practical conditions.

Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

- *Eye protection: Safety glasses Tightly sealed goggles*

- *Body protection: Protective work clothing*

GB

(continued on page 6)

according to 1907/2006/EC, Article 31

2312523

Reviewed on: 28/06/2021

Printing date: 28/07/2021

PRODUCT : SUPREMO KLARLACK 3990

(continued of page 5)

SECTION 09: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Appearance:

Form:	Liquid
Colour:	According to product specifica
Odour:	Characteristic Characteristic
Odour threshold:	Not determined.

Change in condition

Boiling point/Boiling range:	77 °C
Flash point:	-1 °C c.c.
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	425 °C
Decomposition temperature:	Not determined.
Self-igniting:	Not determined.
Danger of explosion:	Not determined.
Explosion limits:	
Lower:	1 Vol %
Upper:	11 Vol %
Vapour pressure:	at 20 °C 10,7000 mbar at 50 °C 55,0000 mbar
Density:	0,9500 g/cm3
Solubility in / Miscibility with water:	Not determined.
Viscosity:	
.	Not determined.
.	at 20 °C
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity
- 10.2 Chemical stability
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions
No dangerous reactions known.
- 10.4 Conditions to avoid
No further relevant information available.
- **10.5 Incompatible materials:**
No further relevant information available.
- **10.6 Hazardous decomposition products:**
No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- **Acute toxicity:**
- LD/LC50 values relevant for classification:

141-78-6 ethyl acetate

(continued on page 7)

according to 1907/2006/EC, Article 31

2312523

Reviewed on: 28/06/2021

Printing date: 28/07/2021

PRODUCT : SUPREMO KLARLACK 3990

(continued of page 6)

Oral, LD50: 5620 mg/kg (Rabbit) Inhalative, LC50/4h: 1600 mg/l (rat) Oral, LD50: 13100 mg/kg (rat) Dermal, LD50: >5000 mg/kg (Rabbit) Inhalative, LC50/4h: >21,0 mg/l (rat) Oral, LD50: 4300 mg/kg (rat) Dermal, LD50: 2000 mg/kg (Rabbit) Oral, LD50: 3500 mg/kg (rat) Dermal, LD50: 17800 mg/kg (Rabbit) Oral, LD50: 7872 mg/kg (rat) Oral, LD50: 5050 mg/kg (rat) Oral, LD50: 2460 mg/kg (rat) Dermal, LD50: 3400 mg/kg (Rabbit) Oral, LD50: 7060 mg/kg (rat) Inhalative, LC50/4h: 20000 mg/l (rat) Oral, LD50: 5628 mg/kg (rat) Dermal, LD50: 15800 mg/kg (Rabbit) Oral, LD50: 5045 mg/kg (rat) Dermal, LD50: 12800 mg/kg (Rabbit) Inhalative, LC50/4h: 30 mg/l (rat) Oral, LD50: 10000 mg/kg (rat) Oral, LD50: 5750 mg/kg (rat) Dermal, LD50: 16000 mg/kg (Rabbit) Oral, LD50: 8532 mg/kg (rat) Inhalative, LC50/4h: 35,7 mg/l (rat) Oral, LD50: 3122 mg/kg (rat) Oral, LD50: 7460 mg/kg (rat) Oral, LD50: 790 mg/kg (rat) Dermal, LD50: 3400 mg/kg (Rabbit) Inhalative, LC50/4h: 8000 mg/l (rat)

123-86-4	n-butyl acetate
1330-20-7	xylene
100-41-4	ethylbenzene
80-62-6	methyl methacrylate
868-77-9	2-hydroxyethyl methacrylate
78-83-1	butanol
64-17-5	ethanol
67-56-1	methanol
67-63-0	propan-2-ol
7631-86-9	silicon dioxide, chemically prepared
108-83-8	2,6-dimethylheptan-4-one
108-65-6	2-methoxy-1-methylethyl acetate
5593-70-4	titanium tetrabutanolate
546-68-9	titanium tetraisopropanolate
71-36-3	butan-1-ol

• **Primary irritant effect:**

• on the skin:
No irritant effect.

• on the eye:
Irritating effect.

• **Sensitization:**
No sensitising effects known.

• **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant

SECTION 12: Ecological information

- **12.1 Toxicity**
- Aquatic toxicity:
No further relevant information available.
- **12.2 Persistence and degradability**
No further relevant information available.
- **Behaviour in environmental systems:**
- **12.3 Bioaccumulative potential**
No further relevant information available.
- 12.4 Mobility in soil
No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
- **12.5 Results of PBT and vPvB assessment**
- **PBT:**
Not applicable.
- **vPvB:**
Not applicable.
- **12.6 Other adverse effects**
No further relevant information available.

2312523

Reviewed on: 28/06/2021
Printing date: 28/07/2021

PRODUCT : SUPREMO KLARLACK 3990

(continued of page 7)

SECTION 13: Disposal considerations

• **13.1 Waste treatment methods**

• **European and swiss waste code**

08

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

08 01

wastes from MFSU and removal of paint and varnish

08 01 11

waste paint and varnish containing organic solvents or other hazardous substances

• **Uncleaned packaging:**

• **Recommendation:**

Disposal must be made according to official regulations.

SECTION 14: Transport information

• **14.1 UN-Number**

ADR UN1263

IMDG UN1263

IATA UN1263

• **14.2 UN proper shipping name**

ADR 1263 PAINT

IMDG PAINT

IATA PAINT

• **14.3 Transport hazard class(es)**

ADR

Class 3 Flammable liquids.

Label

3



IMDG

Class

3 Flammable liquids.

Label

3



IATA

Class

3 Flammable liquids.

Label

3



• **14.4 Packing group**

ADR II

IMDG II

(continued on page 9)

according to 1907/2006/EC, Article 31

2312523

Reviewed on: 28/06/2021

Printing date: 28/07/2021

PRODUCT : SUPREMO KLARLACK 3990

(continued of page 8)

IATA II

- **14.5 Environmental hazards:**

Not applicable.

- **14.6 Special precautions for user**

Warning: Flammable liquids.

Danger code (Kemler): 33

EMS Number: F-E,S-E

- **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

- **Transport/Additional information:**

Not applicable.

Excepted quantities (EQ): E2

Limited quantities (LQ) 5L

Transport category 2

Tunnel restriction code D/E

IMDG
Limited quantities (LQ) 5L

Excepted quantities (EQ) E2

- **UN "Model Regulation":**

UN 1263 PAINT, 3, II

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **REGULATION (EC) No 1907/2006 ANNEX XVII**

Conditions of restriction: 3, 30

- **National regulations:**

- **Classification according to VbF:**

-

- **Technical instructions (air):**

- **Class Share in %**

III 37, 87

II 11, 34

I 0, 04

- **Waterhazard class:**

Water hazard class 2 (Self-assessment): hazardous for water.

- **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

EUH066 Repeated exposure may cause skin dryness or cracking.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

(continued on page 10)

according to 1907/2006/EC, Article 31

2312523

Reviewed on: 28/06/2021

Printing date: 28/07/2021

PRODUCT : SUPREMO KLARLACK 3990

(continued of page 9)

H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

- **Department issuing MSDS:**

Environment protection department.

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VbF: Verordnung über brennbare Flüssigkeiten, Österreich (Ordinance on the storage of combustible liquids, Austria)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

- * *Data compared to the previous version altered.*