

MATERIAL SAFETY DATA SHEET
according to 1907/2006/EC, Article 31

2994711

Reviewed on: 21.05.2019

Printing date: 21.05.2019

SECTION 01: Identification of the substance/mixture and of the company undertaking

- **1.1 Product identifier**
- *Trade name:*
ALPOCRYL BESCHLEUNIGER 6396-00 FOR SOLVENT-BORNE VARNISH
- Article number / Safety Data Sheet:
Z63960
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- Application of the substance / the preparation
Coating material
- **1.3 Details of the supplier of the safety data sheet**
- *Manufacturer/Supplier:*
Teknos Feyco AG
Industriestrasse 3
LI-9487 Gamprin-Bendern
T +423 375 94 00
F +423 375 94 99
- *Further information obtainable from:*
Product safety department.
e-mail address: li-sdb@teknos.com
- **1.4 Emergency telephone number:**
Swiss Toxicological Information Centre
Emergency telephone: +41 (0)44 251 51 51

SECTION 02: Hazards identification

- **2.1 Classification of the substance or mixture**
- Classification according to Regulation (EC) No 1272/2008



GHS02

Flam. Liq. 3 - H226 Flammable liquid and vapour.



GHS07

STOT SE 3 - H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms



GHS02



GHS07

- Signal word
Warning

- Hazard-determining components of labelling:
n-butyl acetate
- Hazard statements
H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
- Precautionary statements
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
* P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
* P403+P233 Store in a well-ventilated place. Keep container tightly closed.

(continued on page 2)

MATERIAL SAFETY DATA SHEET
according to 1907/2006/EC, Article 31

2994711

Reviewed on: 21.05.2019

Printing date: 21.05.2019

PRODUCT : ALPOCRYL BESCHLEUNIGER 6396-00 FOR SOLVENT-BORNE VARNISH

(continued of page 1)

P501 Dispose of contents/container in accordance with local/regional/ national/international regulations.

- **2.3 Other hazards**
- Results of PBT and vPvB assessment
- PBT:
Not applicable.
- vPvB:
Not applicable.

SECTION 03: Composition/information on ingredients

- **3.2 Chemical characterization: Mixtures**
- Description:
Mixture of substances listed below with nonhazardous additions.

- Dangerous components:

CAS Number		%
123-86-4	<i>n</i> -butyl acetate EC number: 204-658-1 Record number 01-2119485493-29 ⚠ Flam. Liq. 3 - H226; ⚠ STOT SE 3 - H336	90,00-100,00
3648-18-8	Di- <i>n</i> -octylzinndilaurat EC number: 222-883-3 ⚠ Acute Tox. 4 - H302; ⚠ Repr. 2 - H361; Aquatic Chronic 3 - H412	0,50- 1,00

SECTION 04: First aid measures

- 4.1 Description of first aid measures
- **After inhalation:**
Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water.
- **After swallowing:**
Do not induce vomiting; call for medical help immediately.
- **Information for doctor:**
- 4.2 Most important symptoms and effects, both acute and delayed
No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
No further relevant information available.

SECTION 05: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:**
Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:**
Mouth respiratory protective device.
Do not inhale explosion gases or combustion gases.
- **Additional information**
Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

MATERIAL SAFETY DATA SHEET
according to 1907/2006/EC, Article 31

2994711

Reviewed on: 21.05.2019

Printing date: 21.05.2019

PRODUCT : ALPOCRYL BESCHLEUNIGER 6396-00 FOR SOLVENT-BORNE VARNISH

(continued of page 2)

SECTION 06: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 07: Handling and storage

- **Handling:**
 - **7.1 Precautions for safe handling**
Take note of emission threshold.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
 - **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
 - **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
 - **Requirements to be met by storerooms and receptacles:**
Store only in the original receptacle.
 - **Information about storage in one common storage facility:**
Not required.
 - **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **7.3 Specific end use(s)**
No further relevant information available.

SECTION 08: Exposure controls/personal protection

- **8.1 Control parameters**
- * • **Ingredients with limit values that require monitoring at the workplace:**

123-86-4	n-butyl acetate		
WEL			
	Short-term value	966	mg/m3
		200	ppm
	Long-term value	724	mg/m3
		150	ppm
- **Additional information:**
The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
The usual precautionary measures are to be adhered to when handling chemicals.
Do not eat or drink while working.
Be sure to clean skin thoroughly after work and before breaks.
- **Respiratory protection:** Suitable respiratory protective device recommended.

(continued on page 4)

MATERIAL SAFETY DATA SHEET
according to 1907/2006/EC, Article 31

2994711

Reviewed on: 21.05.2019

Printing date: 21.05.2019

PRODUCT : ALPOCRYL BESCHLEUNIGER 6396-00 FOR SOLVENT-BORNE VARNISH

(continued of page 3)

- *Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Impervious gloves*
- *Material of gloves*
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- *Penetration time of glove material*
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.
- *Eye protection: Safety glasses Tightly sealed goggles*
- *Body protection: Protective work clothing*

SECTION 09: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Appearance:

Form:	Liquid
Colour:	According to product specifica
Odour:	Characteristic Characteristic
Odour threshold:	Not determined.

Change in condition

Initial boiling point and boiling range:	124 °C
* Flash point:	27 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	425 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Not determined.
Explosive properties:	Not determined.
Explosion limits:	
Lower:	1 Vol %
Upper:	7 Vol %
Vapour pressure:	at 20 °C 10,7000 mbar at 50 °C 55,0000 mbar
Density:	0,8800 g/cm3
Solubility in / Miscibility with water:	Not determined.
Viscosity:	
.	Not determined.
.	at 23 °C

9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

- * **10.1 Reactivity**
No further relevant information available.
- * **10.2 Chemical stability**
- * **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- * **10.3 Possibility of hazardous reactions**
No dangerous reactions known.
- * **10.4 Conditions to avoid**
No further relevant information available.

(continued on page 5)

MATERIAL SAFETY DATA SHEET
according to 1907/2006/EC, Article 31

2994711

Reviewed on: 21.05.2019

Printing date: 21.05.2019

PRODUCT : ALPOCRYL BESCHLEUNIGER 6396-00 FOR SOLVENT-BORNE VARNISH

(continued of page 4)

- **10.5 Incompatible materials:**
No further relevant information available.
- **10.6 Hazardous decomposition products:**
No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**
- *LD/LC50 values relevant for classification:*
- **123-86-4 n-butyl acetate**
Oral, LD50: 13100 mg/kg (rat)
Dermal, LD50: >5000 mg/kg (Rabbit)
Inhalative, LC50/4h: >21 mg/l (rat)
- * *Primary irritant effect:*
- Skin corrosion/irritation
No irritant effect.
- Serious eye damage/irritation
No irritating effect.
- *Respiratory or skin sensitisation*
No sensitising effects known.

SECTION 12: Ecological information

- **12.1 Toxicity**
- Aquatic toxicity:
No further relevant information available.
- **12.2 Persistence and degradability**
No further relevant information available.
- **Behaviour in environmental systems:**
- **12.3 Bioaccumulative potential**
No further relevant information available.
- **12.4 Mobility in soil**
No further relevant information available.
- **Additional ecological information:**
- *General notes:*
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
- **12.5 Results of PBT and vPvB assessment**
- **PBT:**
Not applicable.
- **vPvB:**
Not applicable.
- **12.6 Other adverse effects**
No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **European and swiss waste code**
08
WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01
wastes from MFSU and removal of paint and varnish
08 01 11
* waste paint and varnish containing organic solvents or other hazardous substances
- **Uncleaned packaging:**
- **Recommendation:**

(continued on page 6)

MATERIAL SAFETY DATA SHEET
according to 1907/2006/EC, Article 31

2994711

Reviewed on: 21.05.2019

Printing date: 21.05.2019

PRODUCT : ALPOCRYL BESCHLEUNIGER 6396-00 FOR SOLVENT-BORNE VARNISH

Disposal must be made according to official regulations.

(continued of page 5)

SECTION 14: Transport information

- **14.1 UN-Number**

ADR UN1263

IMDG UN1263

IATA UN1263

- **14.2 UN proper shipping name**

ADR 1263 PAINT RELATED MATERIAL

IMDG PAINT RELATED MATERIAL

IATA PAINT RELATED MATERIAL

- **14.3 Transport hazard class(es)**

ADR

Class 3 Flammable liquids.

Label 3



IMDG

Class 3 Flammable liquids.

Label 3



IATA

Class 3 Flammable liquids.

Label 3



- **14.4 Packing group**

ADR III

IMDG III

IATA III

- **14.5 Environmental hazards:**

Not applicable.

- **14.6 Special precautions for user**

Warning: Flammable liquids.

Danger code (Kemler): 30

EMS Number: F-E,S-E

- **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

- **Transport/Additional information:**

Not applicable.

Exempted quantities (EQ): E1

Limited quantities (LQ): 5L

Transport category 3

(continued on page 7)

MATERIAL SAFETY DATA SHEET
according to 1907/2006/EC, Article 31

2994711

Reviewed on: 21.05.2019

Printing date: 21.05.2019

PRODUCT : ALPOCRYL BESCHLEUNIGER 6396-00 FOR SOLVENT-BORNE VARNISH

(continued of page 6)

Tunnel restriction code D/E**IMDG****Limited quantities (LQ)** 5L**Excepted quantities (EQ)** E1

- **UN "Model Regulation":**
UN 1263 PAINT RELATED MATERIAL, 3, III

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- Regulation (EU) No 649/2012
* 3648-18-8 Di-n-octylzinndilaurat : Annex I Part 1
- **REGULATION (EC) No 1907/2006 ANNEX XVII**
* Conditions of restriction: 3, 40
- **National regulations:**
- **Classification according to VbF:**
-
- **Technical instructions (air):**
- **Class Share in %**
III 99,00
- **Waterhazard class:**
Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **15.2 Chemical safety assessment:**
A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H412	Harmful to aquatic life with long lasting effects.
- **Department issuing MSDS:**
Environment protection department.
- **Abbreviations and acronyms:**
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VbF: Verordnung über brennbare Flüssigkeiten, Österreich (Ordinance on the storage of combustible liquids, Austria)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
- * Data compared to the previous version altered.